

FLX15

15 Watt LED Light Fixture
Track, Surface and Suspended

Job Information	
Project Name	
Type	
Location	
Quantity	
Date	

Description

15W FLEX series is a high performance LED luminaire with powerful output of 1480 lumens, 95 CRI and smooth sharp cylindrical body with no visible heat sink. Lower energy consumption with crisp, precise CCT, beam control with excellent CRI for various lighting applications, from residential to retail lighting.

Features

Body

Constructed of aluminum, the body features an aesthetically pleasing smooth cylindrical shape.

LED Characteristics

High powered 15W CREE® CXA1512 LED array maintains uniform intensity with a typical luminous flux up to 1350 lumens, with a typical CRI of 95.

Beam Spread

Fixture lens options available in 15°, 25°, 40° and 60° beam spread.

Mounting Options

Multiple mounting options for various applications. Available mounting options

include direct mounting onto a 4" octagonal junction box for flushmount and pendant applications, direct mounting onto a 3½" or 4" octagonal junction box for monopoint applications, and 1- or 2-circuit track connectors for track applications (compatible with A-Line, 2- and 3-circuit Powergear, H-style, L-style and Liteline tracks).

CCT	LUMENS
2700 K	1,220
3000 K	1,280
3500 K	1,340
4000 K	1,480

Operating Conditions

For indoor use only.

Quickship Made-To-Order


Made-To-Order products ship within seven business days of an order being released.



SPECIFICATION

Approved Location	Dry / Indoor
Beam Angle	15° / 25° / 40° / 60°
CCT	2700 K / 3000 K / 3500 K / 4000 K
Certification	cETLus
Class II	Yes
Color	BK / SL / WH
CRI	95
Dimming	Yes
Input	100-135V AC, 60Hz
Lumens	Up to 1480
Lumens per Watt	Up to 98
Power Factor	0.95
Projected Life	70% @ 50,000 hrs
Warranty	5 years
Wattage	15W

Technical Drawings



Ordering Guide

Connector Type ¹	Color Temperature	Beam Angle	Mounting Type	Finish	Cord Length ^{1,2}	Rod Length ^{1,2}
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
BLANK : No connector	27 : 2700 K	15 : 15°	F : Flushmount	BK : Black	Blank : Standard 5'	Blank : None
A : A-Line	30 : 3000 K	25 : 25°	M : Monopoint	SL : Silver	120 : 10' / 120"	12 : 12"
H : H-style	35 : 3500 K	40 : 40°	P : Pendant	WH : White		24 : 24"
L : L-style	40 : 4000 K	60 : 60°	T : Track			36 : 36"
LL : Liteline			TP : Track Pendant			48 : 48"
P2 : 2-Circuit Powergear						
P3 : 3-Circuit Powergear						



Highlighted option denotes Quickship.

Notes:

¹ Available for Mounting Type "T" and "TP" only. ² Select option from Cord Length or Rod Length for use with Mounting Type "P" or "TP". Do not combine both options. Quickship option is available on orders of 100 pieces or less, and will ship within 7 business days. Options must be selected from Quickship section to qualify. Accessories are sold separately. For additional options please consult your Liteline representative. Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Liteline Corporation
Copyright © 2021
All rights reserved.

Telephone
416.996.1856
1.866.730.7704

Fax
905.709.5255
1.888.738.9736

LITELINE.COM

Accessories



FLX15-BD-xx¹
Barn doors accessory to facilitate shaping of the light beam. Available in Black (BK), Silver (SL) and White (WH).



FLX15-HC-xx
Honeycomb louver to reduce glare from light source. Available in Black (BK), Silver (SL) and White (WH).



FLX15-SN-xx
Snoot to reduce glare and focuses projected light from light source. Available in Black (BK), Silver (SL) and White (WH).



FLX15-SNO-xx¹
Oval snoot to reduce glare and shape the coverage of the illuminated area. Available in Black (BK), Silver (SL) and White (WH).



FLX15-EXT-xx²
4" Extender. Available in Black (BK), Silver (SL) and White (WH).



FLX15-LINEAR-LENS
Linear spread lens.




FLX15-SL-LENS
Soft lens.

Notes:

¹ Not recommended for use with Mounting Options "F", "P" and "TP". ² Not recommended for use with Mounting Options "M" and "T".

Photometry

FLX15-3040 : FLEX fixture, 15W, 3000 K, 40° beam spread.



Beam Details

D	Lux	FC	L	W
4'	1829	170	2.4'	2.4'
8'	457	42	4.8'	4.8'
12'	203	19	7.2'	7.2'
16'	114	11	9.7'	9.7'
20'	73	7	12.1'	12.1'

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	463.0	37.70%
0-40	673.0	54.80%
0-60	956.0	77.85%
60-90	147.0	11.97%
70-100	93.4	7.61%
90-120	53.1	4.32%
0-90	1103.0	89.82%
90-180	81.7	6.65%
0-180	1228.0	100.00%