

Goof Rings

For 4^{3/8}" (2575), 4" (2000), 3^{3/4}" (2550) and 3^{1/2}" (3000).



When the outside diameter cut is larger than necessary or if the gypsum cracked or broke in the surrounding area of the hole, the goof ring will come in handy. You can match them to the color of your trim or ceiling.

SERIES	CODES	DIMENSIONS	
		Outside diameter	Inside diameter
4" - 2000	RON 2000	ø 6 ^{1/8} "	ø 4 ^{1/8} "
3 ^{3/4} " - 2550/3600 series	RON 2550	ø 5"	ø 3 ^{5/8} "
4 ^{3/8} " - 2575 series	RON 2575	ø 7"	ø 4 ^{9/16} "
3 ^{1/2} " - 3000 series	RON 3000	ø 6 ^{1/8} "	ø 3 ^{5/8} "

All goof rings are available in Contrast finishes. Add finish code at the end.
Ex.: RON2000-**12BR**

Opening Adaptor

For 3^{1/2}" (3000) series.

Can lip adaptor for 3^{1/2}" Pot in a 4^{1/4}" (108mm) opening.
Color N/A (galvanized steel)
Code: **312296**

DIMENSIONS	
Outside diameter	Inside diameter
ø 4 ^{5/16} " (110mm)	ø 3 ^{5/8} " (92mm)

Marine Grade Treatment

Available for Contrast trims.

This treatment is offered with our trim collection of finishes -01, -02, -05, -06, -11, -14 and -15. Unless otherwise indicated, all trim series are for interior use only. For exterior use, «Marine Grade» treatment is recommended. This procedure increases rust resistance up to 5 times more than the untreated galvanized steel. Furthermore, the high temperature powder coated paint process provides a durable finish.

The «Marine Grade» treatment is recommended for very high level humidity locations and is particularly efficient in high salinity areas such as coastal regions. It may be used for outdoors such as soffits and porches, or for indoors, in high humidity or wet areas such as spas, saunas, showers, pool, etc. This treatment is offered with a Contrast limited warranty of two (2) years.

