amphora pendant


DESCRIPTION

A simple modern spun-metal shade references industrial lighting of the post-war manufacturing boom of the 1940s. Its smooth lines and rolled edges create a clean, distinctive look for residential or commercial lighting applications. Includes 6' of field-cuttable black/white cloth cord. Incandescent includes (1) E26 medium base 53 watt A19 lamp; fluorescent includes (1) GX24Q-3 base 32 watt triple tube compact fluorescent lamp. Fluorescent may also be lamped with (1) GX24Q-3 base 26 watt triple tube compact fluorescent lamps (not included). LED includes (1) E26 medium base A19 9.5 watt 800 lumen 80 CRI 2700K LED lamp. Flourescent not dimmable. Incandescent dimmable with a standard incandescent dimmer. LED dimmable with LED compatible dimmer. 120v or 277v.



WEIGHT

1lb / 0.45kg ±









gloss white/brushed aluminum

ORDERING INFORMATION

type	mode	l color	lamp
LP	844	ALWH brushed aluminum/gloss white WHAL gloss white/brushed aluminum	2D E26 A19 53w 120v CF GX24Q-3 32w Triple Tube 120v CF277 GX24Q-3 32w Triple Tube 277v LFD827 F26 LFD A19 9 5 watt 80 CRI 2700K 120v

FIXTURE TYPE:	
JOB NAME:	
NOTES:	



7400 Linder Avenue Skokie, Illinois 60077

T 847.626.6300 F 847.626.6350

www.lbllighting.com



©2016 LBL Lighting. All Rights Reserved. The "LBL Lighting" graphic is a registered trademark of LBL Lighting. LBL Lighting reserves the right to change specifications for product improvements without notification.